

PRESSURE REGULATORS

**Senninger Pressure Regulators**

- Maintain a constant preset outlet pressure while handling inlet pressures up to 150 psi.
- Withstand severe water hammer.
- 100% water tested for accuracy; no adjustments ever needed.
- Strong, durable construction.
- Very low hysteresis and friction losses.
- 3/4" NPT female x 3/4" NPT female thread.
- Two-year warranty on materials, workmanship, and performance.

**Pivot Special Regulator (PSR)<sup>™</sup>  
Multi-Range Pressure Regulator**

Flow Range: 0.5 to 15 gpm.  
Inlet x Outlet: 3/4" Female NPT x 3/4" Female NPT



NI Part#	PSI	Flow in gpm
90139	6	.5 – 15
90135	10	.5 – 15
90142	12	.5 – 15
90133	15	.5 – 15
90132	20	.5 – 15
90136	25	.5 – 15
90134	30	.5 – 15
90137	35	.5 – 15
90140	40	.5 – 15
90117	50	.5 – 15
90151	60	.5 – 15

**Pressure-Master Regulators<sup>®</sup>**

**PMR<sup>®</sup> – Low-Flow Models**

Flow Range: 0.1 to 8 gpm.  
Inlet x Outlet: 3/4" Female NPT x 3/4" Female NPT

NI Part #	PSI	Flow In gpm
90124	6	.5 – 5
90107	10	.5 – 5
90143	12	.1 – 8
90108	15	.1 – 8
90103	20	.1 – 8
90130	25	.1 – 8
90106	30	.1 – 8
90144	35	.1 – 8
90145	40	.1 – 8



**PMR<sup>®</sup> – Medium-Flow Models**

Flow Range: 4 to 16 gpm.  
Inlet x Outlet: 3/4" Female NPT x 3/4" Female NPT



NI Part #	PSI	Flow In gpm
90125	6	4 – 16
90104	10	4 – 16
90146	12	2 – 20
90109	15	2 – 20
90110	20	2 – 20
90111	25	2 – 20
90112	30	2 – 20
90113	35	2 – 20
90114	40	2 – 20
90115	50	2 – 20
90147	60	2 – 20

**PMR<sup>®</sup> – High-Flow Models**

Flow Range: 10 to 32 gpm.  
Inlet x Outlet: 1-1/4" Female NPT x 1" Female NPT

NI Part #	PSI	Flow In gpm
90131	10	10 – 32
90148	15	10 – 32
90123	20	10 – 32
90149	25	10 – 32
90126	30	10 – 32
90116	40	10 – 32
90138	50	10 – 32