

PUMPS

Berkeley Pump Summary



| Pump Description | Capacity | Head Pressure | Horsepower |
|-------------------------------------|-----------------|---|---------------------------|
| Type C Close-Coupled Electric Drive | Up to 175 gpm | Up to 150 ft. | Maximum: 3 |
| Type B Close-Coupled Electric Drive | Up to 5,000 gpm | Up to 500 ft. | 3 to 200 |
| Frame Mount End-Suction Centrifugal | Up to 5,400 gpm | Up to 485 ft. | Up to 235 |
| Self-Priming Centrifugal | Up to 760 gpm | Up to 170 ft. | Maximum: 15 |
| Air-Cooled Engine Drive | 20 to 700 gpm | 25 to 320 ft. | 3 to 30 |
| SAE Engine-Mount | 50 to 5,500 gpm | Up to 550 ft. | Recommended: 15 to 235 |
| PTO Drive Centrifugal | Up to 3,250 gpm | Up to 450 ft. | Up to 85 |
| Series 6A Submersible | Up to 130 gpm | Up to 1,740 ft. | 1.5 to 30 |
| Series 6TP Submersible | Up to 375 gpm | Up to 1,300 ft. | 5 to 60 |
| Series T Submersible | Up to 2,200 gpm | Up to 1,350 ft. | 5 to 200 |
| Vertical Multi-Stage | 1.2 to 115 gpm | Suction Dis- charge Size: 1¼" to 2" | .5 to 25 |

Call our sales office for more information on these and other types of pumps.

114 PH: 402-564-1514 • FAX: 402-563-2792 • Columbus, Nebraska • nebraskairrigation.com